

# ED628



- ▶ Excellent performance for a heavier work with better driving & braking ability, tear, cut and wear resistance.
- ▶ All position tires for the vehicles operating on the blended road or paved road in short or medium distance.



Size	PR	LI/SS	Type	Standard Rim	Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)	Load		Pressure	
								S(kg)	D(kg)	S(kPa)	D(kPa)
9.5R17.5	18	143/141K	T/L	6.75	850	240	16.5	2725	2575	875	875
12R22.5	18	152/148K	T/L	9.00	1085	300	21	3550	3150	850	850
265/70R19.5	18	143/141K	T/L	7.50	873	262	15	2725	2575	900	900
315/80R22.5	20	157/154J	T/L	9.00	1082	312	18.5	4125	3750	900	900
7.50R16	14	122/118L	T/T	6.00G	815	215	15.5	1500	1320	770	770
8.25R16	16	128/124L	T/T	6.50H	865	235	15.5	1800	1600	770	770
8.25R20	16	139/137K	T/T	6.50	974	236	17	2430	2300	930	930
9.00R20	16	144/142K	T/T	7.00	1030	259	18	2800	2650	900	900
11.00R20	18	152/149K	T/T	8.00	1096	293	19.5	3550	3250	930	930
12.00R20	18	154/151K	T/T	8.50	1136	315	20.5	3750	3450	830	830
12.00R24	20	160/157K	T/T	8.50	1226	315	20.5	4500	4125	900	900