

EA828



- ▶ 3-groove with large-angle rib design gives the tire adapt to all axle position and can be used in most of different roads: High way, regional and on/off road.
- ▶ Specialized rubber formula in shoulder utilizes the heat-releasing performance, speeds-up the heat-conduction process and reduces the degradation of rubber caused by heat.
- ▶ Optimaized 4-belt structure reinforces the stiffness of tire cap, minimizes the deformation and contributes to high durability.
- ▶ Optimized tread formula provides excellent anti-wear characteristic to increase overall mileage performance.



Size	PR	LI/SS	Type	Standard Rim	Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)	Load		Pressure	
								S(kg)	D(kg)	S(kPa)	D(kPa)
11R22.5	16	148/145M	T/L	8.25	1054	279	16	3150	2900	840	840
11R24.5	16	149/146M	T/L	8.25	1104	279	16	3250	3000	830	830
12R22.5	18	152/148K	T/L	9.00	1085	300	16.5	3550	3150	850	850
13R22.5	18	154/150L	T/L	9.75	1124	326	15	3750	3350	850	850
295/80R22.5	18	152/149L	T/L	9.00	1044	298	17	3550	3250	900	900
315/80R22.5	20	156/153K	T/L	9.00	1076	312	14	4000	3650	850	850
7.00R16	14	118/114L	T/T	5.50F	775	200	11.5	1320	1180	770	770
7.50R16	14	122/118L	T/T	6.00G	805	215	12.5	1500	1320	770	770
8.25R16	16	128/124L	T/T	6.50H	855	235	12.5	1800	1600	770	770
8.25R20	16	139/137K	T/T	6.50	974	236	13.5	2430	2300	930	930
9.00R20	16	144/142K	T/T	7.00	1019	259	15	2800	2650	900	900
10.00R20	18	149/146K	T/T	7.50	1054	278	16	3250	3000	930	930