



## DYNA COMFORT ES83

UTQG: 500/A/B  
 Speed Rating: T/H/V/Y  
 Rim Range: 15"-18"  
 Aspect Ratio: 50-75



New anti-resistant formula and creative pattern design provide exceptional wet grip, shorten the braking distance, and ensure longer mileage and safer driving.

Inch	Size	LI / SI	Overall Diameter		Section Width		Standard Rim	Max. Load	Max. Pressure	SIDEWALL
			mm	inch	mm	inch		kg	kpa	
15"	205/70R15	96H	669	26.3	209	8.2	6J	710	300	BSW
	235/75R15	105T	733	28.9	235	9.3	6½J	925	300	OWL
	215/65R16 XL	102H	686	27.0	221	8.7	6½J	850	340	BSW
	215/70R16	100T/H	708	27.9	221	8.7	6½J	800	300	BSW
	225/70R16	103T	722	28.4	228	9.0	6½J	875	300	OWL
	235/60R16	100H	688	27.1	240	9.4	7J	800	300	BSW
16"	235/70R16	106T/H	736	29.0	240	9.4	7J	950	300	OWL
	245/70R16 XL	111T	750	29.5	248	9.8	7J	975	300	OWL
	245/70R16 XL	111H	750	29.5	248	9.8	7J	1090	340	OWL
	245/75R16	111T	774	30.5	240	9.4	7J	850	300	OWL
	255/70R16	111T	764	30.1	260	10.2	7½J	1090	300	OWL
	265/70R16	112T	778	30.6	272	10.7	8J	1120	300	OWL
	265/75R16	116T	804	31.7	267	10.5	7½J	1250	300	OWL
	215/60R17	96H	690	27.2	221	8.7	6½J	710	300	BSW
17"	225/60R17	99H	702	27.6	228	9.0	6½J	775	300	BSW
	225/65R17	102T/H	724	28.5	228	9.0	6½J	850	300	BSW
	235/55R17	99V	690	27.2	245	9.6	7½J	775	300	BSW
	235/65R17	104T	738	29.1	240	9.4	7J	900	300	BSW
	235/65R17 XL	108H	738	29.1	240	9.4	7J	1000	340	BSW
	245/65R17 XL	111T	750	29.5	248	9.8	7J	975	300	OWL
	245/70R17	110T	776	30.6	248	9.8	7J	1060	300	OWL
	265/65R17	112T	776	30.6	272	10.7	8J	1120	300	BSW
18"	265/70R17	115T	804	31.7	272	10.7	8J	1215	300	OWL
	225/55R18	98V	705	27.8	233	9.2	7J	750	300	BSW
	235/55R18	100V	715	28.1	245	9.6	7½J	800	300	BSW
	235/60R18	103V	739	29.1	240	9.4	7J	875	300	BSW
	245/60R18	105H	751	29.6	248	9.8	7J	925	300	BSW
	255/55R18 XL	109Y	737	29.0	265	10.4	8J	1030	340	BSW
	255/70R18	113T	815	32.1	260	10.2	7½J	1150	300	BSW
	255/65R18	111T	789	31.1	260	10.2	7½J	1090	300	BSW
19"	265/60R18	110T	775	30.5	272	10.7	8J	1060	300	BSW
	265/65R18	114T	801	31.5	272	10.7	8J	1180	300	BSW
	275/65R18	116T	815	32.1	279	11.0	8J	1250	300	OWL
	255/50R19 XL	107V	739	29.1	265	10.4	8J	975	340	BSW
20"	265/50R20	107V	774	30.5	277	10.9	8½J	975	300	BSW
	275/55R20 XL	117T	810	31.9	284	11.2	8½J	1285	340	BSW
	275/60R20	115T	838	33.0	279	11.0	8J	1215	300	OWL