



## DYNAMASTER EV516

R/T Rated  
60/65/70/75 Series



The unique pattern design provides outstanding handling on wet surfaces and excellent high-speed durability.

Inch	Size	LI / SI	P R	Overall Diameter		Section Width		Standard Rim	Max. Load		Max. Pressure
				mm	inch	mm	inch		S(kg)	D(kg)	
14"	165/70R14C	89/87T	6	588	23.1	170	6.7	5J	580	545	375
	175/65R14C	90/88T	6	584	23.0	177	7.0	5J	600	560	375
15"	195R15C	106/104R	8	693	27.3	196	7.7	5½J	950	900	450
	215/70R15C	109/107R	8	683	26.9	221	8.7	6½J	1030	975	450
	225/70R15C	112/110R	8	697	27.4	228	9.0	6½J	1120	1060	450
16"	185/75R16C	104/102R	8	684	26.9	184	7.2	5J	900	850	475
	205/65R16C	107/105T	8	672	26.5	209	8.2	6J	975	925	475
	215/60R16C	108/106T	8	664	26.1	221	8.7	6½J	1000	950	475
	215/65R16C	109/107R	8	686	27.0	221	8.7	6½J	1030	975	475
	215/75R16C	113/111R	8	728	28.7	216	8.5	6J	1150	1090	475
	225/65R16C	112/110R	8	698	27.5	228	9.0	6½J	1120	1060	475
	235/65R16C	115/113T	8	712	28.0	240	9.4	7J	1215	1150	475
	235/65R16C	121/119R	10	712	28.0	240	9.4	7J	1215	1150	475